



LIGHT TRUCK MUDDER APPLICATION CHART

Tire Size	Wheel Size	Size
33 x10.50	15	E-4 oz.
33x11.50	15	E-4 oz.
33x12.50	15	D-6 oz.
33x14	15	D-6 oz.
33x14.5	15	D-6 oz.
33x15.5	15	D-6 oz.
34x9.5	15	E-4 oz.
34x12.5	15	D-6 oz.
35x12.5	15	D-6 oz.
35x14.5	15	D-6 oz.
35x15	15	D-6 oz.
35x16	15	C-8 oz.
36x14.5	15	D-6 oz.
36x15.5	15	C-8 oz.
36x16.5	15	C-8 oz.
37x12.5	15	D-6 oz.
38x12.5	15	D-6 oz.
38.5x11	15	D-6 oz.
38.5x15.5	15	C-8 oz.
38.5x16	15	C-8 oz.
38.5x16.5	15	C-8 oz.
39x15	15	C-8 oz.
39.5x18	15	C-8 oz.
40x17	15	C-8 oz.
42x15	15	C-8 oz.
44x18.5	15	B-10 oz.
44x19.5	15	B-10 oz.
44x21	15	B-10 oz.
Q78	15	E-4 oz.
33x11.50	16	E-4 oz.
33x12.5	16	D-6 oz.

Tire Size	Wheel Size	Size
33x13	16	D-6 oz.
33x13.5	16	D-6 oz.
34x9	16	E-4 oz.
34x12.5	16	D-6 oz.
35x12.50	16	D-6 oz.
35x14.50	16	D-6 oz.
36x13	16	D-6 oz.
36x14	16	D-6 oz.
36x14.50	16	D-6 oz.
38x15.50	16	C-8 oz.
38.5x11.00	16	D-6 oz.
38.5x14.5	16	C-8 oz.
39.5x15	16	C-8 oz.
40x14.5	16	C-8 oz.
42x15	16	C-8 oz.
44x21	16	B-10 oz.
255/85	16	E-4 oz.
325/80	16.5	D-6 oz.
33x12.50	16.5	D-6 oz.
33x14.00	16.5	D-6 oz.
33x15.50	16.5	D-6 oz.
34x9.50	16.5	E-4 oz.
35x12.5	16.5	D-6 oz.
35x14.50	16.5	D-6 oz.
35x15	16.5	D-6 oz.
35x16	16.5	C-8 oz.
36x12.50	16.5	D-6 oz.
36x14.50	16.5	D-6 oz.
37x12.50	16.5	D-6 oz.
38x12.50	16.5	D-6 oz.
38x15.50	16.5	C-8 oz.

Tire Size	Wheel Size	Size
38.5x15	16.5	C-8 oz.
38.5x16	16.5	C-8 oz.
39.5x15	16.5	C-8 oz.
39.5x18	16.5	C-8 oz.
42x15	16.5	C-8 oz.
44x18.5	16.5	B-10 oz.
44x19.5	16.5	B-10 oz.
49x21	16.5	A-12 oz.
33x12.5	17	D-6 oz.
35x12.5	17	D-6 oz.
37x12.50	17	D-6 oz.
38x15.50	17	C-8 oz.
38.5x14.50	17	C-8 oz.
39.5x15	17	C-8 oz.
42x15	17	C-8 oz.
44x21	17	B-10 oz.
33x12.50	18	D-6 oz.
35x12.50	18	D-6 oz.
37x13.5	18	D-6 oz.
38x15.50	18	C-8 oz.
38.5x14.50	18	C-8 oz.
33x12.50	20	D-6 oz.
35x12.50	20	D-6 oz.
38.5x14.50	20	C-8 oz.
39.5x15	20	C-8 oz.
44x21	20	B-10 oz.
38x15.50	20	C-8 oz.
39.5x15	20	C-8 oz.
35x12.50	22	D-6 oz.

There are many variables that contribute to vibration in “mudder” tires. Before installing FLEXX, please consider the following sources of vibration, including but not limited to: Proper drive line angle, tire pressure, presence of a lift kit, tire run-out, wheel run-out, extreme side wall flex, tread ripple, and/or a lug pattern that may cause acoustical vibration. These factors, and others, will play a role in the vibration of the vehicle and FLEXX will not correct these conditions. We cannot guarantee the elimination of all vibration sources.



FLEXX
MORE MILES. LESS FUEL

TRUCK TIRES

Tire Size		Wheel Position	
		Single	Dual
7.50	R18	E-4 oz.	D-6 oz.
8.00	R19.5	D-6 oz.	C-8 oz.
9.00	R19.5	D-6 oz.	C-8 oz.
18.00	R19.5	W-16 oz.	
225/70	R19.5	D-6 oz.	C-8 oz.
245/70	R19.5	D-6 oz.	C-8 oz.
265/70	R19.5	D-6 oz.	C-8 oz.
275/70	R19.5	C-8 oz.	B-10 oz.
285/70	R19.5	C-8 oz.	B-10 oz.
295/70	R19.5	C-8 oz.	B-10 oz.
305/70	R19.5	B-10 oz.	A-12oz.
280/75	R19.5	C-8 oz.	B-10 oz.
445/65	R19.5	W-16 oz.	
525/65	R20.5	B+C+C=26 oz.	
615/65	R20.5	A+A+B = 34 oz.	
7.50	R20	C-8 oz.	B-10 oz.
8.25	R20	C-8 oz.	B-10 oz.
9.00	R20	B-10 oz.	A-12oz.
10.00	R20	B-10 oz.	A-12oz.
11.00	R20	A-12oz.	B+E = 14 oz.
12.00	R20	A-12oz.	B+E = 14 oz.
12.50	R20	A-12oz.	B+E = 14 oz.
13/80	R20	A-12oz.	B+E = 14 oz.
14/80	R20	B+E = 14 oz.	W-16 oz.
14.00	R20	W-16 oz.	
16.00	R20	B+B = 20 oz.	
10.00	R22	B-10 oz.	A-12 oz.
11.00	R22	A-12oz.	B+E = 14 oz.
9.00	R22.5	C-8 oz.	B-10 oz.
10.00	R22.5	B-10 oz.	A-12 oz.
11.00	R22.5	B-10 oz.	A-12 oz.
12.00	R22.5	A-12 oz.	B+E = 14 oz.
275/50	R22.5	B-10 oz.	A-12 oz.

Tire Size		Wheel Position	
		Single	Dual
235/70	R22.5	D-6 oz.	C-8 oz.
255/70	R22.5	C-8 oz.	B-10 oz.
11/70	R22.5	B-10 oz.	A-12 oz.
265/70	R22.5	C-8 oz.	B-10 oz.
295/60	R22.5	B-10 oz.	A-12 oz.
275/70	R22.5	B-10 oz.	A-12 oz.
305/70	R22.5	B-10 oz.	A-12 oz.
365/70	R22.5	B+E = 14 oz.	
315/70	R22.5	B-10 oz.	A-12 oz.
245/75	R22.5	C-8 oz.	B-10 oz.
265/75	R22.5	C-8 oz.	B-10 oz.
285/75	R22.5	B-10 oz.	A-12 oz.
295/75	R22.5	B-10 oz.	A-12 oz.
315/75	R22.5	A-12 oz.	B+E = 14 oz.
345/75	R22.5	A-12 oz.	
350/75	R22.5	B+E = 14 oz.	
235/80	R22.5	D-6 oz.	C-8 oz.
255/80	R22.5	C-8 oz.	B-10 oz.
275/80	R22.5	B-10 oz.	A-12 oz.
295/80	R22.5	A-12 oz.	B+E = 14 oz.
305/85	R22.5	A-12 oz.	B+E = 14 oz.
315/80	R22.5	A-12 oz.	B+E = 14 oz.
365/80	R22.5	B+E = 14 oz.	
445/50	R22.5	W-16 oz.	
455/50	R22.5	W-16 oz.	
385/65	R22.5	A-12 oz. hwy	W-16 oz. flotation
425/65	R22.5	W-16 oz.	
435/45	R22.5	B+E = 14 oz.	
445/55	R22.5	W-16 oz.	
445/65	R22.5	W-16 oz.	
495/45	R22.5	W-16 oz.	
15.00	R22.5	A-12 oz. hwy	W-16 oz. flotation
16.50	R22.5	W-16 oz.	



FLEXX
MORE MILES. LESS FUEL

TRUCK TIRES (CONT.)

Tire Size		Wheel Position	
		Single	Dual
18.00	R22.5	W-16 oz.	
11.00	R24	A-12 oz.	B+E = 14 oz.
12.00	R24	B+E = 14 oz.	
14.00	R24	W-16 oz.	
285/75	R24.5	B-10 oz.	A-12 oz.
305/75	R24.5	A-12 oz.	B+E = 14 oz.
315/75	R24.5	A-12 oz.	B+E = 14 oz.
275/80	R24.5	B-10 oz.	A-12 oz.
295/80	R24.5	B-10 oz.	A-12 oz.
11.00	R24.5	B-10 oz.	A-12 oz.
12.00	R24.5	A-12 oz.	B+E = 14 oz.



FLEXX
MORE MILES. LESS FUEL

COMMERCIAL LIGHT TRUCK TIRES



Dual Wheel
Positions



10,000 GVW
Rating

The following tire sizes apply only to light truck tires (must be LT rated) for commercial vehicles with dual wheel positions and a 10,000 GVW rating (Class 3) or higher. Check your load capacity to identify the proper amount for your tires on the chart below.

Tire Size		Load Range	
		B, C, or D	E or Higher
195/70	R15	F-3 oz.	D-6 oz.
195/65	R16	F-3 oz.	D-6 oz.
305/70	R16	C-8 oz.	B-10 oz.
225/75	R16	E-4 oz.	D-6 oz.
245/75	R16	E-4 oz.	D-6 oz.
265/75	R16	D-6 oz.	C-8 oz.
285/75	R16	C-8 oz.	B-10 oz.
295/75	R16	C-8 oz.	B-10 oz.
315/75	R16	C-8 oz.	B-10 oz.
215/85	R16	F-3 oz.	D-6 oz.
225/85	R16	E-4 oz.	D-6 oz.
235/85	R16	E-4 oz.	D-6 oz.
245/85	R16	E-4 oz.	D-6 oz.
255/85	R16	D-6 oz.	C-8 oz.
265/85	R16	D-6 oz.	C-8 oz.
305/85	R16	B-10 oz.	A-12 oz.
7.50	R16	F-3 oz.	D-6 oz.
8.25	R16	E-4 oz.	D-6 oz.
11.00	R16	C-8 oz.	B-10 oz.
245/75	R17	D-6 oz.	C-8 oz.
265/70	R17	D-6 oz.	C-8 oz.
235/80	R17	E-4 oz.	D-6 oz.
315/70	R17	C-8 oz.	B-10 oz.

Tire Size		Load Range	
		B, C, or D	E or Higher
315/70	R17.5	C-8 oz.	B-10 oz.
195/60	R17.5	F-3 oz.	D-6 oz.
205/60	R17.5	F-3 oz.	D-6 oz.
225/60	R17.5	E-4 oz.	D-6 oz.
8.00	R17.5	E-4 oz.	D-6 oz.
8.50	R17.5	E-4 oz.	D-6 oz.
9.00	R17.5	D-6 oz.	C-8 oz.
10.00	R17.5	C-8 oz.	B-10 oz.
11.00	R17.5	B-10 oz.	A-12 oz.
14.00	R17.5	A-12 oz.	W-16 oz.
195/70	R17.5	F-3 oz.	D-6 oz.
215/70	R17.5	E-4 oz.	D-6 oz.
235/70	R17.5	E-4 oz.	D-6 oz.
205/75	R17.5	E-4 oz.	D-6 oz.
215/75	R17.5	E-4 oz.	D-6 oz.
225/75	R17.5	E-4 oz.	D-6 oz.
235/75	R17.5	D-6 oz.	C-8 oz.
205/80	R17.5	E-4 oz.	D-6 oz.
225/80	R17.5	E-4 oz.	D-6 oz.
225/90	R17.5	D-6 oz.	C-8 oz.
245/70	R18	D-6 oz.	C-8 oz.
275/65	R18	D-6 oz.	C-8 oz.